



MTP SERIES VFD SYSTEMS

EIM MODEL	LOAD HP	LOAD AMPS	DESCRIPTION	DISTRIBUTOR PRICING
MTP007-480	7.5	12	480VAC THREE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$
MTP010-480	10	16	480VAC THREE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$
MTP015-480	15	23	480VAC THREE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$
MTP020-480	20	30	480VAC THREE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$
MTP025-480	25	37	480VAC THREE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$
MTP030-480	30	45	480VAC THREE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$
MTP040-480	40	61	480VAC THREE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$
MTP050-480	50	78	480VAC THREE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$
MTP060-480	60	92	480VAC THREE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$
MTP075-480	75	107	480VAC THREE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$
MTP100-480	100	142	480VAC THREE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$
MTP150-480	150	216	480VAC THREE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$

**Call
For
Pricing**

**** RATINGS ABOVE ARE FOR 40C (104F) APPLICATIONS. UNITS INSTALLED IN DIRECT SUNLIGHT OR EXCEED 40C (104F) NEED TO BE UPSIZED TO OUR 50C (122F) MODELS. *** CONSULT FACTORY FOR PRICE*****

EIM MODEL	LOAD HP	LOAD AMPS	DESCRIPTION	DISTRIBUTOR BASE PRICING
MTP007-240	7.5	22	240VAC THREE PHASE INPUT, 240VAC THREE PHASE OUTPUT	\$
MTP010-240	10	28	240VAC THREE PHASE INPUT, 240VAC THREE PHASE OUTPUT	\$
MTP015-240	15	42	240VAC THREE PHASE INPUT, 240VAC THREE PHASE OUTPUT	\$
MTP020-240	20	54	240VAC THREE PHASE INPUT, 240VAC THREE PHASE OUTPUT	\$
MTP025-240	25	68	240VAC THREE PHASE INPUT, 240VAC THREE PHASE OUTPUT	\$
MTP030-240	30	80	240VAC THREE PHASE INPUT, 240VAC THREE PHASE OUTPUT	\$
MTP040-240	40	104	240VAC THREE PHASE INPUT, 240VAC THREE PHASE OUTPUT	\$
MTP050-240	50	130	240VAC THREE PHASE INPUT, 240VAC THREE PHASE OUTPUT	\$
MTP060-240	60	154	240VAC THREE PHASE INPUT, 240VAC THREE PHASE OUTPUT	\$
MTP075-240	75	192	240VAC THREE PHASE INPUT, 240VAC THREE PHASE OUTPUT	\$
MTP100-240	100	248	240VAC THREE PHASE INPUT, 240VAC THREE PHASE OUTPUT	\$

**Call
For
Pricing**

**** RATINGS ABOVE ARE FOR 40C (104F) APPLICATIONS. UNITS INSTALLED IN DIRECT SUNLIGHT OR EXCEED 40C (104F) NEED TO BE UPSIZED TO OUR 50C (122F) MODELS. *** CONSULT FACTORY FOR PRICE*****

OPTIONAL FEATURES

PRESSURE TRANSDUCERS 4-20MA	DISTRIBUTOR PRICING
0-100 PSI RATED	\$
10M SHIELDED CABLE	\$