MSP SERIES PHASE CONVERTING VFD SYSTEMS



EIM MODEL	LOAD HP	LOAD AMPS	DESCRIPTION	DISTRIBUTOR PRICING
MSP010-480	5	8	480VAC SINGLE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$
MSP015-480	7.5	12	480VAC SINGLE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$
MSP020-480	10	16	480VAC SINGLE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$
MSP030-480	15	23	480VAC SINGLE PHASE INPUT, 480VAC THREE PHASE OUTPUT	S Call
MSP040-480	20	30	480VAC SINGLE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$ Gatt
MSP050-480	25	37	480VAC SINGLE PHASE INPUT, 480VAC THREE PHASE OUTPUT	For
MSP060-480	30	45	480VAC SINGLE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$ FOI
MSP075-480	40	61	480VAC SINGLE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$ D
MSP100-480	50	78	480VAC SINGLE PHASE INPUT, 480VAC THREE PHASE OUTPUT	^{\$} Pricing
MSP125-480	60	92	480VAC SINGLE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$
MSP150-480	75	107	480VAC SINGLE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$
MSP200-480	100	142	480VAC SINGLE PHASE INPUT, 480VAC THREE PHASE OUTPUT	\$

*** RATINGS ABOVE ARE FOR 40C (104F) APPLICATIONS. UNITS INSTALLED IN DIRECT SUNLIGHT OR EXCEED 40C (104F) NEED TO BE UPSIZED TO OUR 50C (122F) MODELS. *** CONSULT FACTORY FOR PRICE***

EIM MODEL	LOAD HP	LOAD AMPS	DESCRIPTION	DISTRIBUTOR BASE PRICING
MSP010-240	5	15	240VAC SINGLE PHASE INPUT, 240VAC THREE PHASE OUTPUT	\$
MSP015-240	7.5	22	240VAC SINGLE PHASE INPUT, 240VAC THREE PHASE OUTPUT	\$
MSP020-240	10	28	240VAC SINGLE PHASE INPUT, 240VAC THREE PHASE OUTPUT	\$ Call
MSP030-240	15	42	240VAC SINGLE PHASE INPUT, 240VAC THREE PHASE OUTPUT	Gall
MSP040-240	20	54	240VAC SINGLE PHASE INPUT, 240VAC THREE PHASE OUTPUT	\$
MSP050-240	25	68	240VAC SINGLE PHASE INPUT, 240VAC THREE PHASE OUTPUT	For
MSP060-240	30	80	240VAC SINGLE PHASE INPUT, 240VAC THREE PHASE OUTPUT	\$
MSP075-240	40	104	240VAC SINGLE PHASE INPUT, 240VAC THREE PHASE OUTPUT	Pricing
MSP100-240	50	130	240VAC SINGLE PHASE INPUT, 240VAC THREE PHASE OUTPUT	\$
MSP125-240	60	154	240VAC SINGLE PHASE INPUT, 240VAC THREE PHASE OUTPUT	\$
MSP150-240	75	192	240VAC SINGLE PHASE INPUT, 240VAC THREE PHASE OUTPUT	\$

** RATINGS ABOVE ARE FOR 40C (104F) APPLICATIONS. UNITS INSTALLED IN DIRECT SUNLIGHT OR EXCEED 40C (104F) NEED TO BE UPSIZED TO OUR 50C (122F) MODELS. *** CONSULT FACTORY FOR PRICE**

OPTIONAL FEATURES

PRESSURE TRANSDUCERS 4-20MA	DISTRIBUTOR PRICING	
0-100 PSI RATED	\$	
10M SHIELDED CABLE	\$	